

Bar Booster™



PIERESEARCH



Bar Boosters™ are designed to support a reinforcing steel cage within a drilled shaft with a 3" concrete cover requirement. Faulty placement of the cage may cause foundation failure, which often leads to issues of contingent liability. Because the rebar cage cannot be inspected or tested after the concrete is placed in the drilled shaft, the cage must be properly supported at the outset.

Bar Boosters™ are made of durable, noncorrosive plastic and attach to rebar of any size. Each Bar Booster™ has a capacity of 1,500 lbs. The zip tie used for attachment is made of 170 lb. tensile strength resin.

Bar Boosters™ are also great for supporting reinforcing steel over waterproofing, in mat foundations and providing vertical support of slurry wall mats.

Installation:

Installation is accomplished in seconds by simply positioning the Bar Booster™ on the end of a vertical bar of the cage and pulling the zip tie taut. The recommended spacing for installation is one Bar Booster™ attached to the bottom of *every other* vertical bar of the rebar cage.

PIERESEARCH

501 E. Main St.
Arlington, TX 76010
817-265-0980 • 800-342-2409 • FAX 817-275-2335
sales@piereseach.com or stanagee@piereseach.com

Exclusive Manufacturer's Representative

Stanley D. Agee/The Stan Agee Company
2808 Millbrook Ct., Arlington, TX 76012
817-994-1050 • 800-342-2409 • FAX 817-275-2335
www.piereseach.com